

# SP1000 Ambient CO2 Smart Probe

#### Test Products International, Inc.



Uses NDIR CO2 sensor for accuracy Connects to smart phone and uses the TPI Smart Probe App or the TPI View app



Perform ambient CO2 level checks 3 Year Limited Warranty EN50543 compliant

## **Test the TPI Advanta**

Visit www.tpieurope.com

#### **TABLE OF CONTENTS**

A. Introduction	1
3. Safety Considerations	
C. Specifications	2
D. Instrument Overview	3
E. Maintenance	4
Trouble Shooting	4
G. Accessories	4
H. Warranty	
Replacing Batteries	5

The SP1000 has been tested with the following standards and is in compliance with the council RED directive 2014/53/EU: -

## CE DOC

**Declaration of Conformity** 

We

SUMMIT

58, Gaetbeol-ro, Yeonsu-Gu, Incheon, Korea

DECLARE ON OUR SOLE RESPONSIBILITY THAT THE PRODUCT

KIND OF EQUIPMENT : CO2 Mater
TYPE-DESIGNATION : SP1000

This EC-Declaration of conformity is following the provisions of EMC DIRECTIVE 2014/30/EU, RED DIRECTIVE 2014/53/EU.

It is confirmed that a sample of the product has been tested and found in conformity with below standard(s):

EMCD EN 300 328 V2.2.2 EN 301 489-1 V2.1.1

EMC EN 301 489-1 V2.2.3 EN 301 489-17 V3.2.4

Detailed specification of the tested product shown in the following test Report(s):

RF Test Report: 300271-1-4 RF Test Report: 288405-2-2 CE Test Report: KES-EM240526

> Date of issue : 21, March, 2024 Authorized By :

#### A. INTRODUCTION

- Congratulations: Thank you for purchasing TPI products. The SP1000 is easy to use and built to last. It is backed by a 3 year limited warranty.
- Product Description: The SP100 is an Ambient CO2 IAQ
   "Smart Probe". It connects to your mobile device and uses the
   FREE View App to display ambient CO2 readings.
   Data can be displayed, saved, logged, allocated to a specific
   job, exported & e-mailed in either pdf or csv.
- 3. Download the FREE TPI View app from either the Apple App Store or the Google Play Store



#### **B. SAFETY CONSIDERATIONS**

- 1. Never attach the SP1000 to a hot surface.
- Never breath directly into the SP1000 while performing measurement checks as doing so will skew the actual ambient air reading results.
- 3. Do not expose the unit to damp environments for extended periods of time.

#### C. SPECIFICATIONS

SP1000 Smart Probe Ambient Air CO2 Meter Specifications				
Range	0 to 6,000 ppm			
Resolution	1 ppm			
Unit	ppm			
Accuracy	+/- (50ppm+3% of measurement) at (0 to 5,000ppm Range) +/- (100ppm+7% of measurement) at (5,000 to 6,000ppm Range)			
Operating Temperature	0°C to 50°C (32°F to 122°F)			
Storage Temperature	-20°C to 60°C (-4°F to 140°F)			
Measurement Interval	2 seconds			
Communication	Bluetooth version 4.2 (Use with TPI Smart Probe or View app) FCC ID: QOQBDM113 IC: 5123A-GBM113  209-J00204			
Battery Type	AAA x 3 (4.5V)			
Battery Life	30 hours typical			
Weight	99.5 g (3.5 oz)			

The SP1000 has been tested with the following standards and is in compliance with the council RED directive 2014/53/EU: -

EN 300 328 V2.2.2

EN 301 489-1 V2.1.1

EN 301 489-1 V2.2.3

EN 301 489-17 V3.2.4

The relevent certificate can be viewed, downloaded and printed from the TPI website at the following address: -

www.tpieurope.com/wp-content/uploads/2019/11/SP1000-Certificate-of-Conformity.pdf

#### D. INSTRUMENT OVERVIEW



- Sensing area.
- SP1000 status LED indicator.
   Orange and blinking = Bluetooth not connected
   Green and blinking = Bluetooth connected
   Blinking Red with either of the above = Low battery
- 3. Power Key. Press and hold to turn the instrument on. Press and hold to turn the instrument off.

- Built-in magnet. Attach to metal surfaces for hands free operation. Ensure surface is not hot.
- 5. Serial number location. Last three digits are the product identification number and marked in bold. Use this number to distinguish between models when several SP1000's are connected to a phone or tablet.
- 6. Screw to open battery compartment. Turn the screw counter clockwise until it is just above the compartment door. Lift on the screw to open the compartment.



#### E. MAINTENANCE

- 1. Clean the surface of the instrument with a damp cloth.
- 2. Replace the three AAA batteries when the low battery indicator appears.

#### F. TROUBLE SHOOTING

Symptom	Probable Cause
CO2 seems inaccurate.	<ul> <li>Low battery.</li> <li>Make sure not to breath into test area.</li> <li>Ensure connection with smart device is working.</li> </ul>
SP1000 does not turn on.	<ul> <li>Dead or low batteries.</li> </ul>

until unit turns on.
• Defective POWER ON switch.

SP1000 reads high all the time. • Make sure not to breath into test area.

· Not holding down power switch

#### G. ACCESSORIES

Included Accessories		Optional Accessories	
Part Number	Description	Part Number	Description
A1000SP	Soft pouch	A925	Carrying case for 4 smart probes
		A926	Carrying case for 1 or 2 smart probes

#### H. WARRANTY

This product is warranted to the purchaser against defects in material and workmanship for three years from the date of purchase.

**Covered by Warranty:** Repair parts and labor; or replacement of the product at company's option. Normal transportation charges to the purchaser are also covered.

**Not Covered by Warranty:** Damages to the product which are the result of abuse, improper use or maintenance are not covered. Any other expense, consequential damages, incidental damages, or incidental expenses including damages to property are not covered. Transportation expenses to the company are not covered.

**To Obtain Warranty Performance:** Include with the product: your name, address, phone number, written description of the problem and proof of purchase date. Carefully package and return to:

TPI, Inc. 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-520-9197 www.testproductsintl.com TPI Canada 342 Bronte Rd. S., Unit 6 Milton, Ontario L9T 5B7 Canada

905-693-8558 www.tpicanada.com TPI, Europe Ltd..
Unit 6, Rutherford Way Ind. Est.
Rutherford Way, Crawley
West Sussex RH10 9LN England
+44 (0) 1293 530196
www.tpieurope.com

**Implied Warranties:** Any implied warranties including implied warranties of merchantability and fitness for a particular purpose, are limited in duration to three years from date of purchase. To the extent any provision of this warranty is prohibited by federal or state law and cannot be preempted, it shall not be applicable. This warranty gives you specific legal rights, and you may also have other rights which vary from country to country.

#### I. REPLACING BATTERIES

1. Turn the battery compartment screw counter clockwise until it is just above the compartment door. Lift on the screw to open the compartment.



2. Replace the three AAA batteries.



3. Re-install the battery cover and tighten the screw by turning it clockwise.



### Thank You!!!!!



### & Welcome to the TPI Family

We really appreciate you coming onboard, if you aren't already, and look forward to serving you over the next few years, and beyond. For the best experience head over to

www.tpieurope.com,

create your account and register your product.

#### Benefits include:

- **Everything in one place**
- Create service, calibration and warranty/repair requests
- **Download certificates**
- Contact sales, support and customer service
- Read correspondence from TPI including Service updates
- Manage your order history
- Shop Online for accompanying products and spares delivered direct to your door

Please do not hesitate to contact us by any of the following methods:-

Tel: 01293 530196

E-mail: sales@tpieurope.com or service@tpieurope.com

Website: www.tpieurope.com inc. LIVECHAT

Facebook: @tpieurope Twitter: @TPIEuropeLTD













#### Test Products International Europe Ltd. Test Products International (EU) LTD

Unit 6, Rutherford Way Industrial Estate Rutherford Way, Crawley, West Sussex RH10 9LN Tel:: +44 (0) 1293 530196 www.tpieurope.com

Ground Floor, 71 Lower Baggot Street Dublin D02 P593 Ireland